



P.C.B LAYOUT

Technical Data

Material: Brass,machined CuZn38Pb2
 Pin(outer sleeve):Brass,machined CuZn38Pb2
 Plating(outer sleeve):
 Tin Plated: 2μm/80μm"Ni,5μm/200 μ"Sn
 Gold Plated: 2μm"/80 μm"Ni,0.8 μ" gold
 Insuiator: PPS UL94V-0

Electrical:

Current rating: 3Amps/contact max.

Contact resistance: ≤4mΩ/contact

Insulation resistance: ≥1000MΩ at V=100V

Operating voltage: 60VAC/DC

Mechanical:

Mechanical life: min 500 cycle

Operating temperature: -40°C to+105°C

Soldering temperature: +255°C

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	<p>深圳市联丰电子有限公司 SHENZHEN LIANFENG ELECTRONIC CO.,LTD</p>			
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	Duple row socket connector		
CHECKED			2.54mm L=7.64mm H=1.90			
APPROVALS			PART NO.	GP22-2520VV-2XNP-0764A		
TOLERANCES ARE		30~以上	±0.30	ANGLE	UNIT: mm	
		10~30	±0.20		SCALE: 1:1	PROJ:
		5~10	±0.15	±2°	DRAWING NO.	SHEET 1 OF 1
		~ 5	±0.10			